



FEATURES



Dehumidification capacity: 10 l/24h⁽¹⁾
Tank capacity: 1.1 l
Sound power: 36 dB (A)
Humidification level adjustable with mechanic humidistat
Full tank alarm
Constant condensation disposal
Defrosting device
Transparent tank: visible water level
Handle
Maximum volume of dehumidification: 90 m³



AQUARIA 10 is the winner of the GOOD DESIGN AWARD 2014. Founded in Chicago in 1950, GOOD DESIGN is the oldest and most acknowledged international competition for design excellence.



SILENT SYSTEM

AquaRIA 10 is proved to be one of the quietest dehumidifiers in its category, up to 10%⁽²⁾ quieter with just  36 dB (A)  ⁽²⁾



QUICK CONTROL

Mechanic control, extremely easy to use, to adjust ambient humidity.



DOUBLE FRAME

Structural robustness and product solidity are made possible by a system of two overlapping frames, that contain the inside elements, protecting them from collisions.



COMPACT TECHNOLOGY

In just 30 x 25 cm, a dehumidification capacity of 10 l/24h.



(1) 32° C – 80 %RH

(2) Internal tests on the range Olimpia Splendid

| | | AQUARIA 10 |
|---|-----------|----------------------|
| | Code | 01298 |
| | EAN | 8021183012989 |
| Dehumidification capacity (1) | l/24h | 5,1 |
| Dehumidification capacity (2) | l/24h | 10 |
| Humidificable Area | m³ | 90 |
| Heating power | W | - |
| Power consumption in dehumidification (1) | W | 172 |
| Max Power consumption in dehumidification (2) | W | 214 |
| Max Power consumption in dehumidification + heating (2) | W | - |
| Fan speed | | 1 |
| Tank capacity | l | 1,1 |
| Air flow rate (max) | m³/h | 70 |
| Dimensions (Width x H x Depth) | mm | 300 x 365 x 255 |
| Sound level | db(A) | 36 |
| Weight | Kg | 9,5 |
| Refrigerant gas / Charge /GWP* | Type / kg | R410A / 0,075 / 1430 |
| Power supply | V-F-Hz | 230 - 1 - 50 |
| Minimum/maximum power supply voltage | V | 216/244 |
| Air filter | | ✓ |
| Active carbon filter | | |
| Fotocathalitic filter | | |
| HEPA filter | | |
| Operation with continuous drain | | ✓ |
| Mechanical controls | | ✓ |
| Electronic controls | | |
| Mechanical Humidostat | | ✓ |
| Digital Humidostat | | |
| LCD Display | | |
| Backlight LED Display | | |
| Indoor humidity visualizer | | |
| Indoor temperature visualizer | | |
| Tank full light | | ✓ |
| Defrosting device | | ✓ |
| Mot gas defrosting system | | |
| Dehumidifying + heating function (with electrical resistance) | | |
| Handle | | ✓ |
| Wheels | | |
| Tank with push-pull locking | | |
| Tank with handle | | |
| Visible water level | | ✓ |
| Wall mounting kit | | |

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430