



Design by Ercoli & Garlandini

## FEATURES

Dehumidification capacity: 16 l/24h<sup>(1)</sup>  
Tank capacity: 2 l  
Electrical Resistance 1000W  
Sound power: 40 dB (A)  
Digital control  
Drying mode: constant and fast dehumidification  
LCD Display  
Full tank alarm  
Constant condensation disposal  
Electronic defrosting device  
visible water level and transparent tank  
Handle  
Wheels  
Maximum volume of dehumidification: 120-140 m<sup>3</sup>



### PURE SYSTEM

Mechanic air filtration system, for better air quality.



### SUPER DEHUMIDIFICATION

Combines dehumidification with heating thanks to a 1000 W electrical element that significantly reduces dehumidification time.



### DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode, Equipped with back-lit LCD display to view humidity level and ambient temperature.



### COMPACT TECHNOLOGY

In just 25 cm of depth and a height of 45 cm, a dehumidification capacity of 16 l/24h.



### EASY TO USE

Equipped with barycentric and ergonomic handle, and wheels for easier transport.



### TURBO/DRYING

This function optimizes the laundry's drying process by constantly operating the dehumidifier at full power.



(1) 32° C – 80 %RH

		AQUARIA 16T
	Code	01446
	EAN	8021183014464
Dehumidification capacity (1)	l/24h	6,5
Dehumidification capacity (2)	l/24h	16
Humidifiable Area	m³	-
Heating power	W	1000
Power consumption in dehumidification (1)	W	243
Max Power consumption in dehumidification (2)	W	312
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	1,8
Air flow rate ( max )	m³/h	170
Dimensions (Width x H x Depth)	mm	305X464X261
Sound level	db(A)	40
Weight	Kg	12
Refrigerant gas / Charge / GWP*	Type / kg	R410A / 0,130 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	216/244
Air filter		✓
Active carbon filter		
Fotocatalytic filter		
HEPA filter		
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		✓
Dehumidifying + heating function (with electrical resistance)		✓
Handle		✓
Wheels		✓
Tank with push-pull locking		
Tank with handle		
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C ( 27°C - 60% RH )

(2) DB 32°C - WB 29°C ( 32°C - 80% RH )

\*hermetically sealed equipment containing fluorinated gas GWP 1430